according to Regulation (EC) No. 1907/2006

Autoprofi Petrol System Cleaner

Print date: 14.12.2011 Product code: 696 Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Autoprofi Petrol System Cleaner

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaning agent for Fuel Systems

Details of the supplier of the safety data sheet

Company name: CTP-GmbH

Street: Saalfelder Straße 35 Place: D-07338 Leutenberg

Telephone: +4936734/230-0 Telefax: +4936734/230-22

e-mail: hotline@ctp-gmbh.de

Contact person: Jens Moeller, Dipl.-Chem. Telephone: +4936734/230-19

Internet: www.ctp-gmbh.de

Further Information

Article Number: 43211-1

SECTION 2: Hazards identification

Classification of the substance or mixture

Indications of danger: Harmful

R-phrases: Flammable.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Harmful: may cause lung damage if swallowed.

Label elements

Danger symbols: Xn - Harmful



Xn - Harmful

Hazardous components which must be listed on the label

Distillates (petroleum, gasoline), hydrotreated light

R phrases

10 Flammable.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

S phrases

02 Keep out of the reach of children.

46 If swallowed, seek medical advice immediately and show this container or label.

SECTION 3: Composition/information on ingredients

Mixtures

according to Regulation (EC) No. 1907/2006

Autoprofi Petrol System Cleaner

Print date: 14.12.2011 Product code: 696 Page 2 of 9

Chemical characterization

Surface tension compounds Detergents, Dispersants Synthetic agent combinations Anti wear agents not classified

Hazardous components

EC No.	Chemical name	Quantity
CAS No.	Classification	
Index No.	GHS classification	
REACH No.		
265-149-8	Distillates (petroleum, gasoline), hydrotreated light	90 - 95 %
64742-47-8	Xn R10-65	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H336 H304 H411	
	phenole, ethoxylised	1 - 5 %
37205-87-1	Xn, Xi, N R22-41-51-53	
	Acute Tox. 4, Eye Dam. 1, Aquatic Chronic 2; H302 H318 H411	
265-198-5	solvent naphtha	1 - 5 %
64742-94-5	Xn, N R65-66-67-51-53	
	STOT SE 3, Asp. Tox. 1; H336 H304	
202-436-9	1,2,4-trimethylbenzene	< 1 %
95-63-6	Xn, Xi, N R10-20-36/37/38-51-53	
601-043-00-3	Flam. Liq. 3, Acute Tox. 4, Eye Irrit. 2, STOT SE 3, Skin Irrit. 2, Aquatic Chronic 2; H226 H332 H319 H335 H315 H411	
202-049-5	naphthalene	< 1 %
91-20-3	Carc. Cat. 3, Xn, N R40-22-50-53	
601-052-00-2	Carc. 2, Acute Tox. 4, Aquatic Acute 1, Aquatic Chronic 1; H351 H302 H400 H410	

Full text of R- and H-phrases: see section 16.

SECTION 4: First aid measures

Description of first aid measures

General information

Move victim to fresh air. Put victim at rest and keep warm.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

In case of difficulties of breathing consult physician.

If victim is at risk of losing consciousness, position and transport on their side.

After contact with skin

Take off immediately all contaminated clothing, including underwear and shoes .

After contact with skin, wash immediately with plenty of Water and soap.

Rub in high-fat content cream.

After contact with eyes

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Consult physician.

After ingestion

Let water be swallowed in little sips (dilution effect). Consult physician.

Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.

according to Regulation (EC) No. 1907/2006

Autoprofi Petrol System Cleaner

Print date: 14.12.2011 Product code: 696 Page 3 of 9

Irritation of eyes: Irritant effect possible.

After ingestion: Harmful: may cause lung damage if swallowed.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Indication of any immediate medical attention and special treatment needed

Warning about danger of aspiration.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media

Extinguishing powder.

Sand.

alcohol resistant foam.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons

High power water jet.

Special hazards arising from the substance or mixture

Formation of decomposition products possible.

In case of fire and/or explosion do not breathe fumes.

Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Cool endangered container in case of fire.

Contaminated fire-fighting water must be collected separately.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

In case of fire: Wear self-contained breathing apparatus.

Keep away from sources of ignition. No smoking.

Environmental precautions

Beat down gas/vapours/mist with water spray.

Do not empty into drains or the aquatic environment.

In case of gas being released or leakage into waters, ground or the drainage system, the appropriate authorities must be informed.

Methods and material for containment and cleaning up

Prevent spreading of spillages (e.g. by oil barrier).

Wipe up with absorbent material (eg. cloth, fleece).

SECTION 7: Handling and storage

Precautions for safe handling

Advice on safe handling

Closed devices. Vapours / aerosols must be extracted by suction immediately at point of origin.

Avoid contact with skin and eyes.

Advice on protection against fire and explosion

Keep away from sources of ignition. No smoking. Take precautionary measures against static discharges.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

according to Regulation (EC) No. 1907/2006

Autoprofi Petrol System Cleaner

Print date: 14.12.2011 Product code: 696 Page 4 of 9

Further information on storage conditions

Packaging materials: metal.

SECTION 8: Exposure controls/personal protection

Control parameters

Exposure limits (EH40)

CAS No.	Chemical name	ml/m³	mg/m³	F/ml	Category	Origin
91-20-3	Naphthalene	-	-		TWA (8 h)	CHAN
1		-	-		STEL (15 min)	CHAN
95-63-6	Trimethylbenzenes	25	125		TWA (8 h)	WEL
1		-	-		STEL (15 min)	WEL

Exposure controls

Protective and hygiene measures

When using do not eat, drink or smoke.

"Wash hands when done working with material; at breaks, lunch, shift changes, etc."

Respiratory protection

In case of accumulation of fumes/aerosols, provide adequate ventilation.

In case of insufficient ventilation, wear suitable respiratory equipment.

Hand protection

Tested protective gloves are to be worn: Butyl rubber. (EN 374)

Eye protection

Wear tightly sealed safety glasses against possible splashes into the eyes. (EN 166)

Skin protection

Wear suitable solvent-proof protective clothing according to EN 465.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state: liquid
Colour: transparent
Odour: aromatic

Test method

Changes in the physical state

Boiling point:	110 - 116 °C
Flash point:	35 °C
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	12 vol. %
Ignition temperature:	> 200 °C
Vapour pressure:	20 hPa

(at 20 °C)

Density (at 20 °C): 0.78-0.82 g/cm³ Water solubility: insoluble

(at 20 °C)

Solubility in other solvents: Organic solvents

according to Regulation (EC) No. 1907/2006

Autoprofi Petrol System Cleaner

Print date: 14.12.2011 Product code: 696 Page 5 of 9

SECTION 10: Stability and reactivity

Conditions to avoid

Only use material in places where open light, fire and other sources of ignition can be kept away.

Incompatible materials

Oxidizing agents. acid, concentrated. Alkalis (alkalis), concentrated.

Hazardous decomposition products

Carbon monoxide (CO)., Carbon dioxide (CO2).

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

CAS No.	Chemical name					
	Exposure routes	Method	Dose	Species	h	Source
64742-47-8	Distillates (petroleum, gasoline),	Distillates (petroleum, gasoline), hydrotreated light				
	Acute oral toxicity	LD50 mg/kg	>15000	rat.		
	Acute dermal toxicity	LD50	3400 mg/kg	rat.		
	Acute inhalation toxicity	LC50	13100 mg/l	rat.		
37205-87-1	phenole, ethoxylised					
	Acute oral toxicity	LD50	2000 mg/kg	rat.		
64742-94-5	solvent naphtha					
	Acute oral toxicity	LD50	5 mg/kg	rat.		
	Acute dermal toxicity	LD50	>2 mg/kg	Rabbit.		
	Acute inhalation toxicity	LC50	>590 mg/l	rat.	4	
95-63-6	1,2,4-trimethylbenzene					
	Acute oral toxicity	LD50	5000 mg/kg	Ratte		RTECS
	Acute inhalation toxicity	LC50	18 mg/l	Ratte	4	RTECS
91-20-3	naphthalene					
	Acute oral toxicity	ATE	500 mg/kg			

Irritation and corrosivity

After skin contact: Frequently or prolonged contact with skin may cause dermal irritation.

Irritation of eyes: Irritant effect possible.

After ingestion:

Harmful: may cause lung damage if swallowed.

SECTION 12: Ecological information

according to Regulation (EC) No. 1907/2006

Autoprofi Petrol System Cleaner

Print date: 14.12.2011 Product code: 696 Page 6 of 9

Toxicity

CAS No.	Chemical name					
	Aquatic toxicity	Method	Dose	Species	h	Source
64742-47-8	Distillates (petroleum, gasoline), hydrotreated light					
	Acute fish toxicity	LC50	10 mg/l	Oncorhynchus mykiss	96	
	Acute algae toxicity	ErC50	4,6 mg/l	Pseudokirchneriella subcapitata	72	
	Acute crustacea toxicity	EC50	10 mg/l	Daphnia magna	48	
37205-87-1	phenole, ethoxylised					
	Acute fish toxicity	LC50	1-10 mg/l	Brachydanio rerio	96	
	Acute algae toxicity	ErC50	1-10 mg/l	Scenedesmus subspicatus	72	
64742-94-5	solvent naphtha					
	Acute fish toxicity	LC50	2-5 mg/l	Fish	96	
	Acute algae toxicity	ErC50	1-3 mg/l	Algae	72	
	Acute crustacea toxicity	EC50	3-10 mg/l	Daphnia	48	
95-63-6	1,2,4-trimethylbenzene					
	Acute fish toxicity	LC50	7,72 mg/l	Pimephales promelas	96	
	Acute crustacea toxicity	EC50	3,6 mg/l	Daphnia	48	ECOTOX Database

Bioaccumulative potential

Swims on the water.

Low potential of bio-accumulation.

Partition coefficient n-octanol/water

CAS No.	Chemical name	Log Pow
95-63-6	1,2,4-trimethylbenzene	3,63

SECTION 13: Disposal considerations

Waste treatment methods

Advice on disposal

Do not dispose with household waste.

Do not empty into drains or the aquatic environment.

Have to add a Special treatment in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Arrange about the exact waste code with the local waste disposal expert.

Contaminated packaging

Contaminated packing must be completely emptied and can be re-used following appropriate cleaning.

Do not pierce, cut up or weld unclean container. (Explosion hazard.)

SECTION 14: Transport information

Land transport (ADR/RID)

UN number: UN1993

<u>UN proper shipping name:</u> FLAMMABLE LIQUID, N.O.S.

Transport hazard class(es):

Packing group:

Hazard label:

3

according to Regulation (EC) No. 1907/2006

Autoprofi Petrol System Cleaner

Print date: 14.12.2011 Product code: 696 Page 7 of 9



Classification code: F1

Special Provisions: 274 601 640E

Limited quantity: 5 L
Transport category: 3
Hazard-no.: 30
Tunnel restriction code: D/E

Inland waterways transport

UN number: UN1993

UN proper shipping name: FLAMMABLE LIQUID, N.O.S.

Transport hazard class(es):

Packing group:

Hazard label:

3



Classification code: F1

Special Provisions: 274 601 640E

Limited quantity: 5 L

Marine transport

UN number: UN1993

UN proper shipping name: FLAMMABLE LIQUID, N.O.S.

Transport hazard class(es):

Packing group:

Hazard label:

3



Marine pollutant:

Special Provisions: 223, 274, 955

Air transport

UN/ID number: UN1993

UN proper shipping name: FLAMMABLE LIQUID, N.O.S.

Transport hazard class(es):3Packing group:IIIHazard label:3



Special Provisions: A3
Limited quantity Passenger: 10 L

IATA-packing instructions - Passenger: 355

according to Regulation (EC) No. 1907/2006

	Autoprofi Petrol System Cleaner	
Print date: 14.12.2011	Product code: 696	Page 8 of 9
IATA-max. quantity - Passenger:	60 L	
IATA-packing instructions - Cargo:	366	
IATA-max. quantity - Cargo:	220 L	
Environmental hazards		
Dangerous for the environment:	no	

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Additional information

Contains:

- < 5 % Phenols and halogenated phenols
- > 30 % hydrocarbons, aliphatic.

National regulatory information

Water contaminating class (D): 2 - water contaminating

SECTION 16: Other information

Full text of R-	nhraege	referred to	o under	sections	2 and 3
ruii text oi R-	ulliases	reierrea t	o unaer	Sections	Z anu s

in text of it-bi	indaca referred to direct acctions 2 direct
10	Flammable.
20	Harmful by inhalation.
22	Harmful if swallowed.
36/37/38	Irritating to eyes, respiratory system and skin.
40	Limited evidence of a carcinogenic effect.
41	Risk of serious damage to eyes.
50	Very toxic to aquatic organisms.
51	Toxic to aquatic organisms.
52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
53	May cause long-term adverse effects in the aquatic environment.
65	Harmful: may cause lung damage if swallowed.
66	Repeated exposure may cause skin dryness or cracking.
67	Vapours may cause drowsiness and dizziness.
III text of H-St	atements referred to under sections 2 and 3

Ful

text of H-Stat	ements referred to under sections 2 and 3
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

The receiver of our product is singulary responsible for adhering to existing laws and regulations.

according to Regulation (EC) No. 1907/2006

Autoprofi Petrol System Cleaner

Print date: 14.12.2011 Product code: 696 Page 9 of 9

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)