

Print date: 12.12.2011	Product code: 562	I	Page 1 of 7		
SECTION 1: Identification of the substance/mixture and of the company/undertaking					
Product identifier					
Air Condition I	Foam Cleaner				
Relevant identified uses of th	ne substance or mixture and uses advised agair	nst			
Use of the substance/mix	ture				
Air conditione	r cleaning agent				
Details of the supplier of the	safety data sheet				
Company name:	PRO-TEC Deutschland				
Street:	Großgeschwenda 51				
Place:	D-07330 Probstzella				
Telephone:	+4936735/444-0	Telefax: +4936735/444-44			
e-mail:	info@pro-tec-deutschland.com				
Contact person:	Jens Möller, DiplChem.				
Internet:	www.pro-tec-deutschland.de				

Further Information

Article Number: 6122

SECTION 2: Hazards identification

Classification of the substance or mixture

Indications of danger : Extremely flammable R-phrases: Extremely flammable.

Label elements

Danger symbols:

F+ - Extremely flammable



F+ - Extremely flammable

R phrases

12

Extremely flammable.

S phrases

- 02 Keep out of the reach of children.
- 23 Do not breathe Aerosol.
- 51 Use only in well-ventilated areas.

Special labelling of certain mixtures

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

SECTION 3: Composition/information on ingredients

<u>Mixtures</u>



Print date: 12.12.2011

Product code: 562

Page 2 of 7

Chemical characterization

Cleaning agent Odour adsorber chelating agent Fragrances

Aerosol propellent: Propane/butane-mixture

Hazardous components

EC No.	Chemical name	Quantity
CAS No.	Classification	
Index No.	GHS classification	
REACH No.		
203-448-7	butane	15 - 20 %
106-97-8	F+ R12	
601-004-00-0	Flam. Gas 1; H220	
200-827-9	propane	5 - 10 %
74-98-6	F+ R12	
601-003-00-5	Flam. Gas 1; H220	
270-325-2	N-Alkyl(C12-16)-N,N-dimethyl-N-benzyl ammonium chloride	< 1 %
68424-85-1	C, Xn, N R22-34-50	
	Acute Tox. 4, Skin Corr. 1B, Aquatic Acute 1; H302 H314 H400	

Full text of R- and H-phrases: see section 16.

SECTION 4: First aid measures

Description of first aid measures

After inhalation

Provide fresh air.

After contact with eyes

After contact with eye rinse immediately with lot of water at least 5 minutes with open eyelid. In case of troubles or persistent symptoms, consult an opthalmologist.

After ingestion

Rinse mouth immediately and drink large quantities of water.

Most important symptoms and effects, both acute and delayed

Irritation of eyes: Irritant effect possible.

: Vapours may cause drowsiness and dizziness.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media

All extinguishing media practicable.

Special hazards arising from the substance or mixture

The product itself is not combustible.

Additional information

Contaminated fire-fighting water must be collected separately.

Contaminated fire-fighting water must not get into the sewerage network.



Print date: 12.12.2011

Product code: 562

Page 3 of 7

SECTION 6: Accidental release measures

Environmental precautions

Provide for good ventilation, when develop aerosols/mist. Keep away from heat.

Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Prevent spreading over great surfaces (e.g. by damming or installing oil booms).

SECTION 7: Handling and storage

Precautions for safe handling

Advice on protection against fire and explosion

No decomposition when used as intended.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Protect against: frost.

SECTION 8: Exposure controls/personal protection

Control parameters

Exposure limits (EH40)

CAS No.	Chemical name	ml/m³	mg/m³	F/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

Exposure controls

Protective and hygiene measures

When using do not eat, drink or smoke.

"Wash hands when done working with material; at breaks, lunch, shift changes, etc."

Hand protection

Wear suitable gloves.

Eye protection

Wear tightly sealed safety glasses against possible splashes into the eyes.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state: Colour:	Aerosol colourless		
Odour:	perfumed		
			Test method
pH-Value (at 20 °C):		10,5	
Changes in the physical state)		
Flash point:		not applicable	
Vapour pressure: (at 20 °C)		< 12 hPa	
Density:		1,00 - 1,01 g/cm³	



Print date: 12.12.2011

Product code: 562

Page 4 of 7

Water solubility:

(at 20 °C)

highly soluble.

SECTION 10: Stability and reactivity

Conditions to avoid

No decomposition when used as intended. Do not store at temperatures under: 3 °C

Incompatible materials

Oxidizing agents, strong. strong acids

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

CAS No.	Chemical name				
	Exposure routes	Method	Dose	Species	h
106-97-8	butane				
	Acute inhalation toxicity	LC50	658 ppm	Ratte	4
68424-85-1	N-Alkyl(C12-16)-N,N-dimethyl-N-benzyl ammonium chloride				
	Acute oral toxicity	LD50	344 mg/kg	rat.	
	Acute dermal toxicity	LD50	3340 mg/kg	Rabbit.	

Further information

Toxicological data are not available.

The classification was undertaken in accordance with the calculation method governed by the Preparations Directive (1999/45/EC).

SECTION 12: Ecological information

Toxicity

CAS No.	Chemical name				
	Aquatic toxicity Method Dose Species h N-Alkyl(C12-16)-N,N-dimethyl-N-benzyl ammonium chloride				
68424-85-1					
	Acute fish toxicity LC50 0,93 mg/l Oncorhynchus mykiss				96
	Acute crustacea toxicity	EC50	0,016 mg/l	Daphnia magna	48

Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No.	Chemical name	Log Pow
106-97-8	butane	2,89

Further information

No data available

SECTION 13: Disposal considerations

Waste treatment methods



Print date: 12.12.2011

Product code: 562

Page 5 of 7

Waste disposal number of waste from residues/unused products

070601 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fats, grease, soaps, detergents, disinfectants and cosmetics; aqueous washing liquids and mother liquors Classified as hazardous waste.

Waste disposal number of used product

070601 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fats, grease, soaps, detergents, disinfectants and cosmetics; aqueous washing liquids and mother liquors Classified as hazardous waste.

Contaminated packaging

Waste disposal according to official state regulations. Cleaned containers may be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>UN number:</u>	UN1950
UN proper shipping name:	AEROSOLS
	Propane/butane-mixture
<u>Transport hazard class(es):</u>	2
Packing group:	-
Hazard label:	2.1
	2
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Transport category:	2
Hazard-no.:	-
Tunnel restriction code:	D
Inland waterways transport	
<u>UN number:</u>	UN1950
	UN1950 AEROSOLS
<u>UN number:</u> UN proper shipping name:	
	AEROSOLS
UN proper shipping name:	AEROSOLS Propane/butane-mixture
UN proper shipping name: Transport hazard class(es):	AEROSOLS Propane/butane-mixture 2
UN proper shipping name: Transport hazard class(es): Packing group:	AEROSOLS Propane/butane-mixture 2
UN proper shipping name: Transport hazard class(es): Packing group:	AEROSOLS Propane/butane-mixture 2
UN proper shipping name: Transport hazard class(es): Packing group:	AEROSOLS Propane/butane-mixture 2
UN proper shipping name: Transport hazard class(es): Packing group: Hazard label:	AEROSOLS Propane/butane-mixture 2 - 2.1
UN proper shipping name: <u>Transport hazard class(es):</u> <u>Packing group:</u> Hazard label: Classification code:	AEROSOLS Propane/butane-mixture 2
UN proper shipping name: Transport hazard class(es): Packing group: Hazard label:	AEROSOLS Propane/butane-mixture 2 - 2.1 2.1 5F
UN proper shipping name: Transport hazard class(es): Packing group: Hazard label: Classification code: Special Provisions:	AEROSOLS Propane/butane-mixture 2 - 2.1 2.1 5F 190 327 344 625
UN proper shipping name: Transport hazard class(es): Packing group: Hazard label: Classification code: Special Provisions: Limited quantity: Marine transport	AEROSOLS Propane/butane-mixture 2 - 2.1 2.1 5F 190 327 344 625
UN proper shipping name: Transport hazard class(es): Packing group: Hazard label: Classification code: Special Provisions: Limited quantity: Marine transport UN number:	AEROSOLS Propane/butane-mixture 2 - 2.1 5F 190 327 344 625 1 L UN1950
UN proper shipping name: Transport hazard class(es): Packing group: Hazard label: Classification code: Special Provisions: Limited quantity: Marine transport	AEROSOLS Propane/butane-mixture 2 - 2.1 5F 190 327 344 625 1 L



Air Condition Foam Cleaner					
Print date: 12.12.2011	Product code: 562	Page 6 of 7			
Transport hazard class(es):	2				
Packing group:	-				
Hazard label:	2, see SP63				
Marine pollutant: Special Provisions: Limited quantity: EmS:	- 63, 190, 277, 327, 344, 959 See SP277 F-D, S-U				
Air transport					
UN/ID number:	UN1950				
UN proper shipping name:	AEROSOLS, flammable Propane/butane-mixture				
Transport hazard class(es):	2.1				
Packing group:	-				
Hazard label:	2.1				
Special Provisions: Limited quantity Passenger:	A145 A167 30 kg G				
IATA-packing instructions - Passenger: IATA-max. quantity - Passenger: IATA-packing instructions - Cargo: IATA-max. quantity - Cargo:	203 75 kg 203 150 kg				
Environmental hazards					
Dangerous for the environment:	no				
SECTION 15: Regulatory information					
Safety, health and environmental regulation	ns/legislation specific for the substance or mixture				
EU regulatory information					
Additional information Contains: Preservatives.					
National regulatory information					
Water contaminating class (D):	1 - slightly water contaminating				
SECTION 16: Other information					
Full text of R-phrases referred to under12Extremely flammable.22Harmful if swallowed.34Causes burns.50Very toxic to aquatic oFull text of H-Statements referred to undLI220	rganisms. der sections 2 and 3				
H220 Extremely flammable gas.					



Print date: 12.12.2011

Product code: 562

Page 7 of 7

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H400 Very toxic to aquatic life.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singulary responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)